

## HEAVY DUTY POWER BANK



# E-JERRYCAN

External Power Source



### Highlights

- ✓ Internal battery full charge (0-100%) in just 2.25 Hours.
- ✓ Light and Display to indicate functions.
- ✓ Emergency Stop Button.
- ✓ Embedded 12V battery charger (7A Max) with 2m charging cables to recharge Flooded, AGM, Li-ion, EFB, and more.
- ✓ Collapsible handle for compact storage design.
- ✓ Heavy Duty wheels for easy mobility in any environment.
- ✓ Provides up to 2.3kW (up to 8 miles) of EV charging in ~ ≤ 40 minutes under optimal conditions.
- ✓ Compatible with Type 1 or Type 2 EV charging connectors.
- ✓ Worldwide Compatibility.

Designed in France / 108 Service Locations Worldwide / High Capacity Production



E-XTAQ EUROPE: +33 (0)1 30 07 13 30 | E-XTAQ USA: 1.877.453.3265 | E-XTAQ.COM | MarketingUSA@e-xteq.com

# E-XTAQ

## HEAVY DUTY POWER BANK



# E-JERRYCAN



### Specifications

#### Dimensions

|                                           |                                                     |
|-------------------------------------------|-----------------------------------------------------|
| Weight                                    | 53 kg / 117 lbs                                     |
| Dimensions<br>(handle lowered)            | L490/ W515/ H735 (mm)<br>L19.3/ W20.3/ W28.9 (inch) |
| Dimensions<br>(handle in higher position) | L490/ W515/ H1060 (mm)<br>L19.3/ W20.3/ W42 (inch)  |
| Wheels                                    | 203mm / 8inch (x2)                                  |

#### Temperature

|                     |                          |
|---------------------|--------------------------|
| Storage Temperature | -10 ~ 45°C<br>14 ~ 113°F |
| Storage Humidity    | <85% RH                  |

#### Working Temperature Range

|                           |                         |
|---------------------------|-------------------------|
| Charging Internal Battery | 5 ~ 40°C<br>41 ~ 104°F  |
| Inverting output          | -5 ~ 40°C<br>23 ~ 104°F |

#### Range

|                  |                                |
|------------------|--------------------------------|
| Main Input Range | 95 - 263 V<br>48 - 63 HZ       |
| Power            | 2,2 kWh<br>230 Vac             |
| Input            | 110 / 240 V<br>50 / 60 Hz      |
| Output           | 230 Vac / 16 A<br>3.6 Kw (max) |

#### Charge

|               |                                                |
|---------------|------------------------------------------------|
| Full recharge | 2.25h Max<br>from 0-100%                       |
| Distance      | 6 - 13 km<br>4 - 8 miles (range in 40 minutes) |
| Cables length | 5m                                             |